

More Compressed Air for Less Energy.

Portable Compressors

MOBILAIR® M118



Versatile

The MOBILAIR® M118 portable screw compressor is designed for heavy-duty civil and commercial construction, demolition, sand blasting, and other site work applications. The M118 delivers 405 cfm at 100 psig with variable pressure from 85 to 145 psig.

Unsurpassed durability

The M118's heavy duty steel chassis and fully galvanized canopy ensure long life even when subjected to the harshest conditions. Both the canopy and solid steel flooring protect the motor, airend, and critical components from dirt, water, and other contaminants. Rugged construction and excellent cooling allow the M118 to operate in temperatures up to 113°F.

Packaged with features

The M118 offers an array of features that make it very user-friendly. Units come standard with an easy to read control panel that is well protected. The fuel tank has a large filler neck with overflow protection for safe, easy filling. The convenient lifting eye and adjustable height tow hitch enable secure transport. A torsion bar suspension system and oversized tires provide superior road handling, further adding to the unit's exceptional functionality.

Low noise

A quiet motor, superior soundproofing, and vibration isolation result in smooth operation and extremely low decibel levels. 76 db(A) maximum at 23 feet.

Standard Features

- SIGMA PROFILE® airend produces more air with less fuel consumption
- Heavy duty diesel engine complies with Tier 4 Final emissions standards
- SIGMA CONTROL® MOBIL 2 integrated controller
- Modulation control with variable pressure up to 145 psig
- Heavy duty steel chassis and fully galvanized canopy
- High capacity cold start battery ensures reliable operation even under extreme working conditions
- · Highly efficient cooling system
- 1 micron, 2-stage compressor inlet filter with maintenance indicator
- 10 micron engine air filter with maintenance indicator
- Lifting eye for simple handling

Optional features:

- Aftercooler and filtration packages
- · Skid mount

Optional 5 year warranty

To protect your investment, all of our MOBILAIR compressors are available with an optional 5 year warranty on the compressor airend.

Technical Specifications

	(COMPRESSOR		DIESEL ENGINE				PACKAGE			DIMENSIONS
	Model	Free Air Delivery (cfm)		Make	Power @ Full Load	Full Load Speed	Off Load Running Speed	Fuel Tank Capacity	Weight (lb.)	Outlets	L* x W x H (in.)
		100 psig	145 psig		(hp)	(rpm)	(rpm)	(gal)			
	M118	405	360	Deutz 3.6L4 Tier 4 Final	114	2050 - 2200	1600	45	4462	3 x 3/4 1 x 1½	188 x 74 x 68

^{*}Length includes tow bar Sound level maximum is 76 db(A) at 23 feet


Specifications subject to change without notice.

Features and Benefits



SIGMA CONTROL® MOBIL 2

In addition to basic operation and fluid level indicators, our advanced controller provides service reminders and stores maintenance and operations history for diagnostics and troubleshooting. A hinged cover protects the panel from sun, debris, and moisture.



Variable pressure control

To meet the needs of different uses like powering breakers, blowing cable, and even higher pressure applications like sand blasting, pressure can be adjusted between 87 and 145 psig.







KAESER Boisbriand, QC 3760 La Verendrye Street

Boisbriand, QC J7H 1R5 Telephone: (450) 971-1414 Toll free: (800) 477-1416 info.canada@kaeser.com

KAESER Surrey, BC

3757 190th Street Surrey, BC V3Z 0P6 Telephone: (604) 516-7821 Toll Free: (800) 477-1416 info.canada@kaeser.com



ISO 9001:2015 ISO 14001:2015 ISO 45001:2018 ISO 50001:2018





KAESER Lévis, QC

103-1194 ch. Industriel Lévis, QC G7A 1B1 Telephone: (450) 971-1414 Toll free: (800) 477-1416 info.canada@kaeser.com

KAESER London, ON

185 Exeter Rd Unit B, London, ON N6L 1A4 Telephone: (226) 721-0070 Toll free: (800) 477-1416 info.canada@kaeser.com