

## **Portable Compressors**

# Mobilair™ M15 / M17



### **Compact and Reliable**

The Mobilair™ M15 and M17 are compact and dependable compressors that deliver 50 and 60 cfm @100 psig, respectively. They are perfect for a variety of applications including light construction, post driving, carpentry, and monument engraving. With a folding handle, oversized pneumatic tires, and compact design, these units are easy to move around virtually any job site.

The M15 and M17 feature Kaeser's power saving Sigma Profile™ airend. This efficient Kaeser design maintains steady pressure and signature performance to

lower your fuel bill by delivering maximum cfm per horsepower. Driving these airends are quiet but powerful Honda engines with modulation control which match air output to load demand. They both have a simple electric starter with keyed ignition and an easy-to-read control panel.

The scratch, dent, and impact resistant rotomolded polyethylene shell takes a beating and still protects the unit. Inside, the compressors are protected by a 4 micron inlet filters rated at 99.9% efficiency, allowing these units to operate in virtually any construction environment.

#### **Standard Features:**

- Single stage, oil injected rotary screw airend with power-saving, proprietary Sigma Profile
- 4-cycle, V-twin industrial duty Honda gasoline engine
- Compressor and engine are disengaged for easy starting, even in cold conditions
- Convenient one-touch electric start
- Control panel displays pressure and hour meter
- Protective rotomolded polyethylene enclosure
- Vibration isolation for smooth, quiet operation
- 4 micron air intake filters protect the airend

## Optional 5 year warranty

To protect your investment, all of our Mobilair compressors are available with an optional 5 year warranty on the compressor airend.

# **Technical Specifications**

(	COMPRESSO	OR	DIESEL ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery (cfm)		Make	Power @ Full Load	Full Load Speed	Off Load Running Speed	Fuel Tank Capacity	Weight (lb.)	Outlets	L x W x H (in.)
	100 psig	217 psig		(hp)	(rpm)	(rpm)	(gal)			. ,
M15	50	_	Honda GX630	14.8	3000	2200	5.3	445	1 x 1/2"	42½ x 31½ x 31
M17	60	35		17.4	2300 - 3300	2000 - 2200		450		

Sound level maximum is 82 db(A) at 23 feet

Specifications subject to change without notice.

# **Outstanding Advantages**

- Contemporary, compact design, fits easily in the back of a pickup truck
- ✓ Single stage, oil injected rotary screw airend with power-saving proprietary Sigma Profile™
- ✓ Heavy-duty Honda engine
- Large 5 gallon fuel tank for extended run-time
- ✓ Extremely low sound level
- ✓ Easy access and serviceability
- Protective rotomolded polyethylene enclosure
- ✓ Lightweight and easy to maneuver
- Available as stationary mount









Built for a lifetime.

# **Kaeser Compressors, Inc.** 511 Sigma Drive

Fredericksburg, VA 22408 USA Telephone: 540-898-5500 Toll Free: 800-777-7873 info.usa@kaeser.com

#### Kaeser Compressors Canada Inc.

3760 La Vérendrye Street Boisbriand, QC J7H 1R5 CANADA Telephone: (450) 971-1414 Toll free: (800) 477-1416 info.canada@kaeser.com

#### Kaeser Compresores de México S de RL de CV

Calle 2 #123
Parque Industrial Juríca
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

#### www.kaeser.com

# Kaeser Compresores de Guatemala y Cia. Ltda.

Calz. Atanasio Tzul 21-00, zona 12 El Cortijo II, Bodega 501 01012-Guatemala City Telephone: +502 2412-6000 info.guatemala@kaeser.com





