

Portable Compressors

Mobilair™ M250



Versatile

The Mobilair™ M250 portable rotary screw compressor is built for many applications including sand-blasting, pavement breaking, and general air tool use. Units are also well suited for rental houses, repair trucks, and railroads.

Packaged with Features

The M250 offers a wide array of features that make it very user-friendly. Units come standard with the Sigma Control Mobil™ instrument panel. The fuel tank has a wide filler neck with overflow protection for safe, easy filling. A height adjustable tow bar, torsion bar suspension system, and oversized tires provide superior road handling, further adding to the unit's exceptional functionality.

Unsurpassed Durability

The M250's heavy duty steel chassis and fully galvanized enclosure protect the motor, airend, and critical components from dirt, water, and other contaminants. This rugged construction combined with superior design allow the M250 to operate in ambient temperatures up to 122°F.

Low Noise

A quiet motor, superior soundproofing, and vibration isolation result in smooth operation and extremely low decibel levels. 76 db(A) maximum at 23 feet.

Standard Features:

- Rotary screw airend: Sigma Profile™ produces more air with less fuel consumption
- Heavy duty Mercedes Benz diesel engine
- Heavy duty steel chassis
- Fully galvanized canopy
- 1 micron, 2-stage compressor and engine inlet filters with maintenance indicator
- High capacity cold start battery ensures reliable operation even under extreme working conditions
- Tool boxes for convenient storage
- Lifting eye for simple handling
- Highly efficient cooling system
- Modulation control

Optional Features:

- Pressures to 205 psig
- Aftercooler and filtration packages
- Skid mount

Technical Specifications

COMPRESSOR					DIESEL ENGINE				PACKAGE			DIMENSIONS
Model	Free Air Delivery at				Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L' x W x H (in.)
	125 psig (cfm)	145 psig (cfm)	175 psig (cfm)	205 psig (cfm)								
M250	900	875	795	705	Mercedes Benz OM926LA	288	1800	1200	66	7760	3 x 3/4" 1 x 2"	225¼ x 77¾ x 89¼

*Length includes tow bar
Sound level maximum is 76 db(A) at 23 feet

Specifications are subject to change without notice.

Outstanding Advantages

- Easy access with gull-wing doors
- Gear driven Sigma Profile™ airend produces more air with less fuel consumption
- Solid state Sigma Control Mobil™ instrument panel
- Heavy-duty Mercedes Benz diesel engine
- Thick soundproofing for super low noise level
- 1 micron compressor air inlet filter with maintenance indicator protects the equipment
- Heavy duty bumpers and lighting kit are standard



Optional 5 Year Warranty

To protect your investment, all of our Mobilair compressors are available with an optional 5 year warranty on the compressor airend.



Sigma Control Mobil™



Built for a lifetime.



www.kaeser.com

Kaeser Compressors, Inc.
511 Sigma Drive
Fredericksburg, VA 22408 USA
Telephone: 540-898-5500
Toll Free: 800-777-7873
info.usa@kaeser.com

Kaeser Compressors Canada Inc.
3760 La Verendrye Street
Boisbriand, QC J7H 1R5 CANADA
Telephone: (450) 971-1414
Toll free: (800) 477-1416
info.canada@kaeser.com

Kaeser Compresores de México S de RL de CV
Calle 2 #123
Parque Industrial Jurídica
76100 Querétaro, Qro.
Telephone: 01 (442) 218 64 48
sales.mexico@kaeser.com

Kaeser Compresores de Guatemala y Cia. Ltda.
Calz. Atanasio Tzul 21-00, zona 12
El Cortijo II, Bodega 501
01012-Guatemala City
Telephone: +502 2412-6000
info.guatemala@kaeser.com

